


# Methods of Joining

## MetFlo® Compression Couplings *Bold Type Designates a Stock Item*

To determine your part number when ordering:

Use **Product ID** plus **Bolts** plus **Gasket** plus **Protector**.



### We Also Carry...

- Replacement Gaskets
- Gasket Protectors
- Static Strips
- Nuts & Bolts

Please Call For Pricing & Information!

Compression couplings are available with and without gasket protectors.

In the protector column:  
11 = with gasket protector  
10 = no gasket protector

### SPECIAL SERVICES

- Shot Peening
- Spiral Grooving
- Porcelain Lining
- Ceramic Coating
- Part Variations

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
1-1/2"	<b>1.500</b>		<b>38.1</b>	<b>1500</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	1.500		38.1	1500	2	B	11	4
	<b>1.500</b>		<b>38.1</b>	<b>1500</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	1.500		38.1	1500	2	W	11	4
	<b>1.500</b>		<b>38.1</b>	<b>1500</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	1.500		38.1	1500	3	B	11	6
	<b>1.500</b>		<b>38.1</b>	<b>1500</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	1.500		38.1	1500	3	W	11	6
1-3/4"	1.750		44.45	1750	2	B	10	4
	1.750		44.45	1750	2	B	11	4
	1.750		44.45	1750	2	W	10	4
	1.750		44.45	1750	2	W	11	4
	<b>1.750</b>		<b>44.45</b>	<b>1750</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	1.750		44.45	1750	3	B	11	6
	<b>1.750</b>		<b>44.45</b>	<b>1750</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	1.750		44.45	1750	3	W	11	6
1-29/32"	1.900	1-1/2"	48.26	1900	2	B	10	4
	1.900	1-1/2"	48.26	1900	2	B	11	4
	1.900	1-1/2"	48.26	1900	2	W	10	4
	1.900	1-1/2"	48.26	1900	2	W	11	4
	<b>1.900</b>	<b>1-1/2"</b>	<b>48.26</b>	<b>1900</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	1.900	1-1/2"	48.26	1900	3	B	11	6
	<b>1.900</b>	<b>1-1/2"</b>	<b>48.26</b>	<b>1900</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	1.900	1-1/2"	48.26	1900	3	W	11	6
2"	<b>2.000</b>		<b>50.8</b>	<b>2000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	2.000		50.8	2000	2	B	11	4
	<b>2.000</b>		<b>50.8</b>	<b>2000</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	2.000		50.8	2000	2	W	11	4
	<b>2.000</b>		<b>50.8</b>	<b>2000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	2.000		50.8	2000	3	B	11	6
	<b>2.000</b>		<b>50.8</b>	<b>2000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	2.000		50.8	2000	3	W	11	6
2-1/8"	<b>2.125</b>		<b>53.975</b>	<b>2125</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	2.125		53.975	2125	2	B	11	4
	<b>2.125</b>		<b>53.975</b>	<b>2125</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	2.125		53.975	2125	2	W	11	4
	<b>2.125</b>		<b>53.975</b>	<b>2125</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	2.125		53.975	2125	3	B	11	6
	<b>2.125</b>		<b>53.975</b>	<b>2125</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	2.125		53.975	2125	3	W	11	6
	2.125		53.975	2125	3	R	10	6
	2.125		53.975	2125	3	R	11	6
2-1/4"	<b>2.250</b>		<b>57.15</b>	<b>2250</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	2.250		57.15	2250	3	B	11	6
	2.250		57.15	2250	3	W	10	6
	2.250		57.15	2250	3	W	11	6



## MetFlo® Compression Couplings *Bold Type Designates a Stock Item*

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
<b>2-3/8"</b>	<b>2.375</b>	<b>2"</b>	<b>60.325</b>	<b>2375</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>2.375</b>	<b>2"</b>	<b>60.325</b>	<b>2375</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	<b>2.375</b>	<b>2"</b>	<b>60.325</b>	<b>2375</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	2.375	2"	60.325	2375	3	W	11	6
	2.375	2"	60.325	2375	4	B	10	8
	2.375	2"	60.325	2375	4	B	11	8
	2.375	2"	60.325	2375	4	W	10	8
	2.375	2"	60.325	2375	4	W	11	8
<b>2-1/2"</b>	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>2</b>	<b>B</b>	<b>11</b>	<b>4</b>
	2.500		63.5	2500	2	W	10	4
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>2</b>	<b>W</b>	<b>11</b>	<b>4</b>
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	2.500		63.5	2500	3	R	10	6
	2.500		63.5	2500	3	R	11	6
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	<b>2.500</b>		<b>63.5</b>	<b>2500</b>	<b>3</b>	<b>W</b>	<b>11</b>	<b>6</b>
	2.500		63.5	2500	4	B	10	8
	2.500		63.5	2500	4	B	11	8
	2.500		63.5	2500	4	W	10	8
	2.500		63.5	2500	4	W	11	8
<b>2-7/8"</b>	<b>2.875</b>	<b>2.5"</b>	<b>73.025</b>	<b>2875</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	2.875	2.5"	73.025	2875	3	B	11	6
	2.875	2.5"	73.025	2875	3	W	10	6
	2.875	2.5"	73.025	2875	3	W	11	6
<b>3"</b>	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	3.000		76.2	3000	2	B	11	4
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	3.000		76.2	3000	2	W	11	4
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>3</b>	<b>W</b>	<b>11</b>	<b>6</b>
	3.000		76.2	3000	3	R	10	6
	3.000		76.2	3000	3	R	11	6
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>4</b>	<b>B</b>	<b>11</b>	<b>8</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	<b>3.000</b>		<b>76.2</b>	<b>3000</b>	<b>4</b>	<b>W</b>	<b>11</b>	<b>8</b>
<b>3-1/2"</b>	<b>3.500</b>	<b>3</b>	<b>88.9</b>	<b>3500</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	3.500	3	88.9	3500	3	B	11	6
	3.500	3	88.9	3500	3	W	10	6
	3.500	3	88.9	3500	3	W	11	6
	<b>3.500</b>	<b>3</b>	<b>88.9</b>	<b>3500</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>

### Coupling Specifications

- 1-1/2" through 14" OD for tube
- 1-1/2" through 8" NPS for pipe
- The MetFlo® Compression Coupling offers superior strength.
- Heavy 16 gauge outer shell on all couplings over 3-1/4" in diameter provides added strength and dimensional stability.
- G90 galvanized exterior coating provides superior corrosion resistance.
- Reinforcement bars are zinc plated steel to provide additional strength and stability.
- Grade 5 stress relieved bolts ensure durability.
- Industry compatible, precision die cut black neoprene gasket ensures a tight seal.
- Stainless steel strip guards against static electricity build-up.

**Stainless steel compression couplings available upon request.**

**Stainless steel gasket protectors are also available.**

#### Other gaskets:

White Nitrile  
Red Rubber  
Silicone  
EPDM  
Viton

**Call for information!**

#### TERMINOLOGY

**CLR** = Center Line Radius  
**ERW** = Electric Welded Resistance  
**FNPT** = Female National Pipe Thread  
**ID** = Inside Diameter  
**MNPT** = Male National Pipe Thread  
**NPS** = Nominal Pipe Size  
**OD** = Outside Diameter  
**SCH** = Schedule

# Methods of Joining


## MetFlo® Compression Couplings

*Bold Type Designates a Stock Item*

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
3-1/2"	3.500	3	88.9	3500	4	B	11	8
	<b>3.500</b>	<b>3</b>	<b>88.9</b>	<b>3500</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	3.500	3	88.9	3500	4	W	11	8
4"	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	4.000	3.5	101.6	4000	2	B	11	4
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	4.000	3.5	101.6	4000	2	W	11	4
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	4.000	3.5	101.6	4000	3	R	10	6
	4.000	3.5	101.6	4000	3	R	11	6
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	4.000	3.5	101.6	4000	3	W	11	6
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>4</b>	<b>B</b>	<b>11</b>	<b>8</b>
<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>	
<b>4.000</b>	<b>3.5</b>	<b>101.6</b>	<b>4000</b>	<b>4</b>	<b>W</b>	<b>11</b>	<b>8</b>	
4-1/2"	4.500	4	114.3	4500	2	B	10	4
	4.500	4	114.3	4500	2	B	11	4
	4.500	4	114.3	4500	2	W	10	4
	4.500	4	114.3	4500	2	W	11	4
	<b>4.500</b>	<b>4</b>	<b>114.3</b>	<b>4500</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	4.500	4	114.3	4500	3	B	11	6
	4.500	4	114.3	4500	3	W	10	6
	4.500	4	114.3	4500	3	W	11	6
	<b>4.500</b>	<b>4</b>	<b>114.3</b>	<b>4500</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	4.500	4	114.3	4500	4	B	11	8
	<b>4.500</b>	<b>4</b>	<b>114.3</b>	<b>4500</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	4.500	4	114.3	4500	4	W	11	8
5"	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	5.000	127	5000	5000	2	B	11	4
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>2</b>	<b>W</b>	<b>10</b>	<b>4</b>
	5.000	127	5000	5000	2	W	11	4
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	5.000	127	5000	5000	3	R	10	6
	5.000	127	5000	5000	3	R	11	6
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	5.000	127	5000	5000	3	W	11	6
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>4</b>	<b>B</b>	<b>11</b>	<b>8</b>
<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>	
<b>5.000</b>	<b>127</b>	<b>5000</b>	<b>5000</b>	<b>4</b>	<b>W</b>	<b>11</b>	<b>8</b>	
5-9/16"	<b>5.563</b>	<b>5</b>	<b>141.3</b>	<b>5563</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	5.563	5	141.3	5563	3	B	11	6
	5.563	5	141.3	5563	3	W	10	6
	5.563	5	141.3	5563	3	W	11	6

To determine your part number when ordering:

Use **Product ID** plus **Bolts** plus **Gasket** plus **Protector**.



### We Also Carry...

- Replacement Gaskets
- Gasket Protectors
- Static Strips
- Nuts & Bolts

Please Call For Pricing & Information!

Compression couplings are available with and without gasket protectors.

In the protector column:  
11 = with gasket protector  
10 = no gasket protector

### SPECIAL SERVICES

- Shot Peening
- Spiral Grooving
- Porcelain Lining
- Ceramic Coating
- Part Variations



## MetFlo® Compression Couplings *Bold Type Designates a Stock Item*

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
<b>5-9/16"</b>	<b>5.563</b>	<b>5</b>	<b>141.3</b>	<b>5563</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	5.563	5	141.3	5563	4	B	11	8
	<b>5.563</b>	<b>5</b>	<b>141.3</b>	<b>5563</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	<b>5.563</b>	<b>5</b>	<b>141.3</b>	<b>5563</b>	<b>4</b>	<b>W</b>	<b>11</b>	<b>8</b>
<b>6"</b>	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>4</b>
	6.000		152.4	6000	2	B	11	4
	6.000		152.4	6000	2	W	10	4
	6.000		152.4	6000	2	W	11	4
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>6</b>
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>3</b>	<b>R</b>	<b>10</b>	<b>6</b>
	6.000		152.4	6000	3	R	11	6
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>6</b>
	6.000		152.4	6000	3	W	11	6
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	6.000		152.4	6000	4	B	11	8
	6.000		152.4	6000	4	R	10	8
	6.000		152.4	6000	4	R	11	8
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	6.000		152.4	6000	4	W	11	8
	<b>6.000</b>		<b>152.4</b>	<b>6000</b>	<b>5</b>	<b>B</b>	<b>10</b>	<b>10</b>
	6.000		152.4	6000	5	B	11	10
6.000		152.4	6000	5	W	10	10	
6.000		152.4	6000	5	W	11	10	
<b>6-5/8"</b>	6.625	6	168.3	6625	3	B	10	6
	6.625	6	168.3	6625	3	B	11	6
	6.625	6	168.3	6625	3	W	10	6
	6.625	6	168.3	6625	3	W	11	6
	<b>6.625</b>	<b>6</b>	<b>168.3</b>	<b>6625</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	6.625	6	168.3	6625	4	B	11	8
	<b>6.625</b>	<b>6</b>	<b>168.3</b>	<b>6625</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>8</b>
	6.625	6	168.3	6625	4	W	11	8
	6.625	6	168.3	6625	5	B	10	10
	6.625	6	168.3	6625	5	B	11	10
	6.625	6	168.3	6625	5	W	10	10
	6.625	6	168.3	6625	5	W	11	10
<b>7"</b>	<b>7.000</b>		<b>177.8</b>	<b>7000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>6</b>
	7.000		177.8	7000	3	B	11	6
	7.000		177.8	7000	3	W	10	6
	7.000		177.8	7000	3	W	11	6
	<b>7.000</b>		<b>177.8</b>	<b>7000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>8</b>
	7.000		177.8	7000	4	B	11	8
	7.000		177.8	7000	4	W	10	8
	7.000		177.8	7000	4	W	11	8
<b>8"</b>	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>2</b>	<b>B</b>	<b>10</b>	<b>6</b>
	8.000		203.2	8000	2	B	11	6

### Coupling Specifications

- 1-1/2" through 14" OD for tube
- 1-1/2" through 8" NPS for pipe
- The MetFlo® Compression Coupling offers superior strength.
- Heavy 16 gauge outer shell on all couplings over 3-1/4" in diameter provides added strength and dimensional stability.
- G90 galvanized exterior coating provides superior corrosion resistance.
- Reinforcement bars are zinc plated steel to provide additional strength and stability.
- Grade 5 stress relieved bolts ensure durability.
- Industry compatible, precision die cut black neoprene gasket ensures a tight seal.
- Stainless steel strip guards against static electricity build-up.

**Stainless steel compression couplings available upon request.**

**Stainless steel gasket protectors are also available.**

#### Other gaskets:

- White Nitrile
- Red Rubber
- Silicone
- EPDM
- Viton

**Call for information!**

#### TERMINOLOGY

- CLR** = Center Line Radius
- ERW** = Electric Welded Resistance
- FNPT** = Female National Pipe Thread
- ID** = Inside Diameter
- MNPT** = Male National Pipe Thread
- NPS** = Nominal Pipe Size
- OD** = Outside Diameter
- SCH** = Schedule

# Methods of Joining


## MetFlo® Compression Couplings

*Bold Type Designates a Stock Item*

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
8"	8.000		203.2	8000	2	W	10	6
	8.000		203.2	8000	2	W	11	6
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>3</b>	<b>B</b>	<b>10</b>	<b>8</b>
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>3</b>	<b>B</b>	<b>11</b>	<b>8</b>
	8.000		203.2	8000	3	R	10	8
	8.000		203.2	8000	3	R	11	8
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>3</b>	<b>W</b>	<b>10</b>	<b>8</b>
	8.000		203.2	8000	3	W	11	8
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>10</b>
	8.000		203.2	8000	4	B	11	10
	8.000		203.2	8000	4	R	10	10
	8.000		203.2	8000	4	R	11	10
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>4</b>	<b>W</b>	<b>10</b>	<b>10</b>
	8.000		203.2	8000	4	W	11	10
	<b>8.000</b>		<b>203.2</b>	<b>8000</b>	<b>5</b>	<b>B</b>	<b>10</b>	<b>12</b>
	8.000		203.2	8000	5	B	11	12
8.000		203.2	8000	5	W	10	12	
8.000		203.2	8000	5	W	11	12	
8-5/8"	8.625	8	219.1	8625	3	B	10	8
	8.625	8	219.1	8625	3	W	10	8
	8.625	8	219.1	8625	4	B	10	10
	8.625	8	219.1	8625	4	W	10	10
9"	9.000		228.6	9000	3	B	10	8
10"	10.000		254.0	10000	3	B	10	8
	10.000		254.0	10000	3	B	11	8
	10.000		254.0	10000	3	R	10	8
	10.000		254.0	10000	3	R	11	8
	10.000		254.0	10000	3	W	10	8
	10.000		254.0	10000	3	W	11	8
	10.000		254.0	10000	4	B	10	10
	10.000		254.0	10000	4	B	11	10
	10.000		254.0	10000	4	R	10	10
	10.000		254.0	10000	4	R	11	10
	10.000		254.0	10000	4	W	10	10
	10.000		254.0	10000	4	W	11	10
	10.000		254.0	10000	5	B	10	12
12"	12.000		304.8	12000	3	B	10	8
	12.000		304.8	12000	3	B	11	8
	12.000		304.8	12000	3	W	10	8
	<b>12.000</b>		<b>304.8</b>	<b>12000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>10</b>
	12.000		304.8	12000	4	B	11	10
	12.000		304.8	12000	4	W	10	10
	12.000		304.8	12000	4	W	11	10
	12.000		304.8	12000	4	W	11	10
	12.000		304.8	12000	5	B	10	12
	12.000		304.8	12000	5	B	11	12

To determine your part number when ordering:

Use **Product ID** plus **Bolts** plus **Gasket** plus **Protector**.



### We Also Carry...

- Replacement Gaskets
- Gasket Protectors
- Static Strips
- Nuts & Bolts

Please Call For Pricing & Information!

Compression couplings are available with and without gasket protectors.

In the protector column:

- 11 = with gasket protector
- 10 = no gasket protector

### SPECIAL SERVICES

- Shot Peening
- Spiral Grooving
- Porcelain Lining
- Ceramic Coating
- Part Variations



## MetFlo® Compression Couplings *Bold Type Designates a Stock Item*

SIZE	ID	NPS SIZE	METRIC	PRODUCT ID	BOLTS	GASKET	PROTECTOR	LENGTH
<b>14"</b>	<b>14.000</b>		<b>355.6</b>	<b>14000</b>	<b>4</b>	<b>B</b>	<b>10</b>	<b>10</b>
	14.000		355.6	14000	4	B	11	10
	14.000		355.6	14000	4	W	10	10
	14.000		355.6	14000	4	W	11	10
	14.000		355.6	14000	5	B	10	12

### Coupling Specifications

- 1-1/2" through 14" OD for tube
- 1-1/2" through 8" NPS for pipe
- The MetFlo® Compression Coupling offers superior strength.
- Heavy 16 gauge outer shell on all couplings over 3-1/4" in diameter provides added strength and dimensional stability.
- G90 galvanized exterior coating provides superior corrosion resistance.
- Reinforcement bars are zinc plated steel to provide additional strength and stability.
- Grade 5 stress relieved bolts ensure durability.
- Industry compatible, precision die cut black neoprene gasket ensures a tight seal.
- Stainless steel strip guards against static electricity build-up.

***Stainless steel compression couplings available upon request.***

***Stainless steel gasket protectors are also available.***

#### **Other gaskets:**

White Nitrile  
Red Rubber  
Silicone  
EPDM  
Viton

**Call for information!**

#### TERMINOLOGY

**CLR** = Center Line Radius  
**ERW** = Electric Welded Resistance  
**FNPT** = Female National Pipe Thread  
**ID** = Inside Diameter  
**MNPT** = Male National Pipe Thread  
**NPS** = Nominal Pipe Size  
**OD** = Outside Diameter  
**SCH** = Schedule