

Methods of Joining




Bold Type Designates a Stock Item

INSTALOK™ Specifications

- 1-1/2" OD to 6" OD
- 20% Lower cost than traditional couplings
- 30% Quicker installation
- Couplings have a unique clamping design that offers unparalleled strength and grip
- Made with Grade 5 stress relieved bolts to ensure durability
- Standard O-ring is black nitrile
- Viton O-rings are also available
- Galvanized Steel Construction

We also offer replacement O-rings, nuts, bolts and clamps



OD	NPS	O-RING	LENGTH	PRODUCT ID
1-1/2"		Black	4"	CP15042B-16Z
1-1/2"		White	4"	CP15042W-16Z
1-1/2"		Black	6"	CP15062B-16Z
1-1/2"		White	6"	CP15062W-16Z
1-3/4"		Black	4"	CP17542B-16Z
1-3/4"		White	4"	CP17542W-16Z
1-3/4"		Black	6"	CP17562B-16Z
1-3/4"		White	6"	CP17562W-16Z
2"		Black	4"	CP20042B-16Z
2"		White	4"	CP20042W-16Z
2"		Black	6"	CP20062B-16Z
2"		White	6"	CP20062W-16Z
2-1/8"		Black	4"	CP21242B-16Z
2-1/8"		White	4"	CP21242W-16Z
2-1/8"		Black	6"	CP21262B-16Z
2-1/8"		White	6"	CP21262W-16Z
2-1/4"		Black	4"	CP22542B-16Z
2-1/4"		White	4"	CP22542W-16Z
2-1/4"		Black	6"	CP22562B-16Z
2-1/4"		White	6"	CP22562W-16Z
2-3/8"	2"	Black	4"	CP237542B-16Z
2-3/8"	2"	White	4"	CP237542W-16Z
2-3/8"	2"	Black	6"	CP237562B-16Z
2-3/8"	2"	White	6"	CP237562W-16Z
2-3/8"	2"	Black	8"	CP237582B-16Z
2-3/8"	2"	White	8"	CP237582W-16Z
2-1/2"		Black	4"	CP25042B-16Z
2-1/2"		White	4"	CP25042W-16Z
2-1/2"		Black	6"	CP25062B-16Z
2-1/2"		White	6"	CP25062W-16Z
2-1/2"		Black	8"	CP25082B-16Z
2-1/2"		White	8"	CP25082W-16Z
2-7/8"	2-1/2"	Black	4"	CP287542B-16Z
2-7/8"	2-1/2"	White	4"	CP287542W-16Z
2-7/8"	2-1/2"	Black	6"	CP287562B-16Z
2-7/8"	2-1/2"	White	6"	CP287562W-16Z
2-7/8"	2-1/2"	Black	8"	CP287582B-16Z
2-7/8"	2-1/2"	White	8"	CP287582W-16Z

Order by Product ID Number Only

SPECIAL SERVICES

- Shot Peening
- Spiral Grooving
- Porcelain Lining
- Ceramic Coating
- Part Variations



INSTALOK™ COUPLINGS

Bold Type Designates a Stock Item


OD	NPS	O-RING	LENGTH	PRODUCT ID
3"		Black	4"	CP30042B-16Z
3"		White	4"	CP30042W-16Z
3"		Black	6"	CP30062B-16Z
3"		White	6"	CP30062W-16Z
3"		Black	8"	CP30082B-16Z
3"		White	8"	CP30082W-16Z
3-1/2"	3"	Black	4"	CP35042B-16Z
3-1/2"	3"	White	4"	CP35042W-16Z
3-1/2"	3"	Black	6"	CP35062B-16Z
3-1/2"	3"	White	6"	CP35062W-16Z
3-1/2"	3"	Black	8"	CP35082B-16Z
3-1/2"	3"	White	8"	CP35082W-16Z
4"	3-1/2"	Black	4"	CP40042B-16Z
4"	3-1/2"	White	4"	CP40042W-16Z
4"	3-1/2"	Black	6"	CP40062B-16Z
4"	3-1/2"	White	6"	CP40062W-16Z
4"	3-1/2"	Black	8"	CP40082B-16Z
4"	3-1/2"	White	8"	CP40082W-16Z
4-1/2"	4"	Black	6"	CP45062B-16Z
4-1/2"	4"	White	6"	CP45062W-16Z
4-1/2"	4"	Black	8"	CP45082B-16Z
4-1/2"	4"	White	8"	CP45082W-16Z
5"		Silicone	8"	CP50082S-16Z
6"		Silicone	8"	CP60082S-16Z

Order by
Product ID Number
Only

INSTALOK™ Dust Cap Specifications

- 1-1/2" OD to 4" OD
- Utilizes the same unique clamping design as the INSTALOK Coupling
- Great for sealing exposed/unused material handling lines
- Non-permanent and completely reusable

We also offer replacement
O-rings, nuts, and bolts



INSTALOK™ Dust Caps

OD	NPS	O-RING	LENGTH	PRODUCT ID
1-1/2"		Black	3"	DC-150-B
1-3/4"		Black	3"	DC-175-B
2"		Black	3"	DC-200-B
2-1/4"		Black	3"	DC-225-B
2-1/2"		Black	3"	DC-250-B
3"		Black	3"	DC-300-B
4"	3-1/2"	Black	3"	DC-400-B

Bold Type Designates
a Stock Item

Order by
Product ID Number
Only

TERMINOLOGY

CLR = Center Line Radius
ERW = Electric Welded Resistance
FNPT = Female National Pipe Thread
ID = Inside Diameter
MNPT = Male National Pipe Thread
NPS = Nominal Pipe Size
OD = Outside Diameter
SCH = Schedule