

Long-Tangent Reducer Couplings *Bold Type Designates a Stock Item*


SIZE	GAUGE	A (OD)	E (OD)	C	D/K	PRODUCT ID
1-1/2" X 2"	16	2"	1-1/2"	6-15/16"	3	RCLT-15X20-3AS
1-3/4" X 2"	16	2"	1-3/4"	6-7/16"	3	RCLT-175X20-3AS
2" X 2-1/4"	16	2-1/4"	2"	6-7/16"	3	RCLT-20X225-3AS
2" X 2-1/2"	16	2-1/2"	2"	6-15/16"	3	RCLT-20X25-3AS
2-1/4" X 2-1/2"	16	2-1/2"	2-1/4"	6-7/16"	3	RCLT-225X25-3AS
2-1/2" X 3"	16	3"	2-1/2"	7-1/2"	3	RCLT-25X30-3AS
2-1/2" X 4"	16	4"	2-1/2"	14-1/4"	4	RCLT-25X40-4AS*

*Welded construction

Order by
Product ID Number
Only


To determine your part number when ordering:

Use **Gauge** plus **Product ID** plus **Material type**.



Material type

A = Aluminum
C = Carbon
S = Stainless



Reducer Coupling Specifications

- 1-1/2" through 4" OD
- Wall Thickness: 16 Gauge
- Aluminum

Offer longer tangent lengths so connection is possible with INSTALOK™ or compression couplings

TERMINOLOGY

CLR = Center Line Radius
ERW = Electric Welded Resistance
FNPT = Female National Pipe Thread
ID = Inside Diameter
MNPT = Male National Pipe Thread
NPS = Nominal Pipe Size
OD = Outside Diameter
SCH = Schedule

All reference dimensions are nominal.