

6" NPS

Bold Type Designates a Stock Item

OD	SCHEDULE (Wall Thickness) & MATERIAL	CLR	DEGREE	PRODUCT ID
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	24	90	600242
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	24	60	600246
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	24	45	600241
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	24	30	600243
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	30	90	600302
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	30	60	600306
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	30	45	600301
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	30	30	600303
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	36	90	600362
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	36	60	600366
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	36	45	600361
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	36	30	600363
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	48	90	600482
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	48	60	600486
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	48	45	600481
6"	10P A, 10P C, 10P S, 40P A, 40P C, 40P S	48	30	600483

• Nominal standard tangent is two times NPS, 6" minimum.

To determine your part number when ordering:

Use **Schedule** plus **Product ID** plus **Material type**.



Material type

A = Aluminum
C = Carbon
S = Stainless

Pipe Bend Specifications

- 2" through 6" NPS
- Radius Options:
 - **Short Radius**
(1-1/2" times NPS)
 - **Standard Radius**
(2-1/2" times NPS)
 - **Long Radius Bends**
(up through 72" CLR)
- Wall Thickness:
Schedule 5, 10 & 40
(Sch. 80 available)
- Aluminum, Carbon & Stainless

TERMINOLOGY

CLR = Center Line Radius
ERW = Electric Welded Resistance
FNPT = Female National Pipe Thread
ID = Inside Diameter
MNPT = Male National Pipe Thread
NPS = Nominal Pipe Size
OD = Outside Diameter
SCH = Schedule